



# ZT3000

## Zero-Turn Mower



The ZT3000 delivers a quality cut no matter how many acres you maintain.

- High-performance Kawasaki® FT series engine
- Ergonomically engineered controls
- Durable, steel-tubed frame
- All-day fuel capacity

STARTING AT  
**\$7,429\* USD**

Rebates up to \$600 USD\*

OR

FINANCE  
**\$124/month\* USD**

0% for 60 months\*



[Search Inventory](#)

[Build & Quote](#)

[Contact Dealer](#)

[View Offers](#)

[Find Dealer](#)

[Download Brochure](#)

## ZT3000 Overview

The ZT3000 is built to handle the toughest jobs with commercial-grade features including the TufDeck™ Pro cutting system and a powerful Kawasaki® FT series engine.

- Say hello to pro-grade performance with innovative cutting technology, heavy-duty torque, high fuel capacity, smooth operation and all-day ride comfort.
- When the job demands more, the ZT3000 is built to handle it with a heavy-duty, steel-tubed frame that's engineered to last.
- Powerful airflow aggressively shoots clippings from an extra-large discharge chute for a cleaner deck and a consistently high-quality cut with three available deck sizes.
- Put your ZT3000 into drive and notice instant power and response from the Hydro-Gear ZT-3100 hydrostatic transaxle drive system that delivers ground speeds up to 8 mph.

## ZT3000 Specs & Compare

ZT3048SC

ZT3061SE

ZT3052SD

## ZT3000 Key Specifications

Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts	TufDeck™ Pro10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts
Width	48 in	61 in	52 in
Cutting Height	1.5-4.875	1.5-4.875	1.5-4.875
Engine Model	Kaw FR651V	Kaw FR730V	Kaw FR691V
Displacement	726 cm <sup>3</sup>	726 cm <sup>3</sup>	726 cm <sup>3</sup>
Transmission type	HG ZT-3100 Hydrostatic Transaxles	HG ZT-3100 Hydrostatic Transaxles	HG ZT-3100 Hydrostatic Transaxles
Pump Displacement	10 cm <sup>3</sup>	10 cm <sup>3</sup>	10 cm <sup>3</sup>

## Deck

Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts	TufDeck™ Pro10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts
Width	48 in	61 in	52 in
Cutting Height	1.5-4.875	1.5-4.875	1.5-4.875
Blade Tip Speed	17,365 ft/min	17,365 ft/min	17,365 ft/min
Discharge Chute	Flexible Molded Polymer	Flexible Molded Polymer	Flexible Molded Polymer

## Engine

Engine Model	Kaw FR651V	Kaw FR730V	Kaw FR691V
Displacement	726 cm <sup>3</sup>	726 cm <sup>3</sup>	726 cm <sup>3</sup>
Fuel Capacity	3.8 gal	3.8 gal	3.8 gal
Horsepower	20 hp	24 hp	22 hp

## Performance

Weight	758 lb	817 lb	774 lb
--------	--------	--------	--------

## Transmission

Transmission type	HG ZT-3100 Hydrostatic Transaxles	HG ZT-3100 Hydrostatic Transaxles	HG ZT-3100 Hydrostatic Transaxles
Pump Displacement	10 cm <sup>3</sup>	10 cm <sup>3</sup>	10 cm <sup>3</sup>
Oil Capacity	4 qt_liq_us	4 qt_liq_us	4 qt_liq_us
Forward Speed	8 mph	8 mph	8 mph
Reverse Speed	3.5 mph	3.5 mph	3.5 mph

Electrical			
Charging System	15 A	15 A	15 A
Clutch	125 ft-lbf	125 ft-lbf	125 ft-lbf

  

Frame			
Front/Rear	Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing	Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing	Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing
Length	76 in	79 in	76 in

  

Wheels			
Drive Wheel	22 x 11.0-10	22 x 11.0-10	22 x 11.0-10
Front Caster Wheel Size	13 x 5.0-6	13 x 5.0-6	13 x 5.0-6
Caster Arm Attachment	Welded to Frame	Welded to Frame	Welded to Frame

  

Seat			
Seat	High-Back, Spring Suspension Seat	High-Back, Spring Suspension Seat	High-Back, Spring Suspension Seat
Fore-Aft Adjust	Seat Slide Lever	Seat Slide Lever	Seat Slide Lever

## ZT3000 Features & Benefits

[Expand all](#) ▾

**Performance** 4 ▾

**Durability** 1 ▾

**Comfort** 1 ▾

**Versatility** 1 ▾

**Serviceability** 1 ▾

## Related Models

[View All Zero-Turn Mowers](#) >

\*The prices advertised are suggested resale prices that Bobcat recommends to dealers for purposes of trying to ensure that Bobcat's products are price-competitive and that dealers have the proper incentives to market and service the products in accordance with Bobcat's brand standards. Bobcat reserves the right to change suggested resale prices, product specifications, and options at any time. The final sales price is determined independently by the selling dealer in its sole discretion. Pricing is country specific. Bobcat's suggested list prices are for products sold in the US only.

\*Offer ends 12/31/2023. Available at participating and eligible dealers only. Offer may vary by product type, series, model and select units in dealer's current inventory. Must take delivery from dealer stock by 12/31/2023. Offers available on new equipment in US and Canada only. Some restrictions apply. Length of contract and rate may vary. Monthly payment subject to change. Prior purchases not eligible. See dealer for details. Financing provided on approval of credit by authorized Bobcat finance providers to well-qualified buyers. All finance programs and rates are subject to final approval by the applicable Bobcat finance provider and are subject to change at any time without notice. Administrative fees may apply. Offer not available to government accounts, national accounts and municipal/utility bid customers. Bobcat Company reserves the right to extend or discontinue any of these programs at any time without prior notice.



**WARNING:** *This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).*

*Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.*