



# ZT6000

## Zero-Turn Mower



- Deluxe suspension seat
- Smooth, responsive controls
- Heavy-duty, dual-tubed frame
- Ground speeds up to 12 mph
- Featuring the [AirFX™ Cutting Deck](#)

STARTING AT  
**\$12,399\* USD**

OR

FINANCE  
**\$207/month\* USD**

Get as Low as 0% For 60 Months\* OR Rebates up to \$1,000 USD\* OR a Free Boss Vac Collection System\*.



[Search Inventory](#)

[Build & Quote](#)

[Contact Dealer](#)

[View Offers](#)

[Find Dealer](#)

[Download Brochure](#)

## ZT6000 Overview

You demand just as much from your machines as you put into your business. Not all zero-turn mowers can live up to that expectation – but the ZT6000 can. With features like an innovative drive system, rugged design and powerful Kawasaki® FX801V engine, the ZT6000 zero-turn mower delivers all you need to make even the toughest jobs look easy.

- The Hydro-Gear ZT-4400 drive system keeps your machine's transaxles performing at optimum output levels with improved control while reducing vibration and noise.
- The bullnose AirFX™ deck delivers a better quality of cut – bar none. Using innovative air-gap baffles and vacuum seal technology, it creates superior airflow and lift on every blade of grass for an impressive quality of cut every time.
- With dual 15-gallon fuel tanks, the ZT6000 zero-turn mower lets you go from job to job without stopping to refuel.

## ZT6000 Specs & Compare

ZT6052SL

ZT6061SL

## ZT6000 Key Specifications

Mower Deck	AirFX™ Cutting System	AirFX™ Cutting System
Width	52 in	61 in
Cutting Height	1-5.5 in.	1-5.5
Engine Model	Kaw FX801V	Kaw FX801V
Displacement	852 cm <sup>3</sup>	852 cm <sup>3</sup>
Transmission type	HG ZT-4400 Hydrostatic Transaxles	HG ZT-4400 Hydrostatic Transaxles
Pump Displacement	12 cm <sup>3</sup>	12 cm <sup>3</sup>

## Deck

Mower Deck	AirFX™ Cutting System	AirFX™ Cutting System
Width	52 in	61 in
Cutting Height	1-5.5 in.	1-5.5
Blade Tip Speed	18,586 ft/min	18,500 ft/min
Discharge Chute	Flexible Molded Polymer	Flexible Molded Polymer

## Engine

Engine Model	Kaw FX801V	Kaw FX801V
Displacement	852 cm <sup>3</sup>	852 cm <sup>3</sup>
Fuel Capacity	15 gal	15 gal
Horsepower	25.5 hp	25.5 hp

## Performance

Weight	1371 lb	1421 lb
--------	---------	---------

## Transmission

Transmission type	HG ZT-4400 Hydrostatic Transaxles	HG ZT-4400 Hydrostatic Transaxles
Pump Displacement	12 cm <sup>3</sup>	12 cm <sup>3</sup>
Oil Capacity	2.5 qt_liq_us	2.5 qt_liq_us
Forward Speed	12 mph	12 mph
Reverse Speed	4 mph	4 mph

## Electrical

Charging System	15 A	15 A
Clutch	225 ft·lbf	225 ft·lbf

Frame		
Front/Rear	Welded 0.25 in, 7-gauge Steel; 1.5 x 2.5 in Steel Tubing	Welded 0.25 in, 7-gauge Steel; 1.5 x 2.5 in Steel Tubing
Length	83 in	83 in

  

Wheels		
Drive Wheel	24 x 10.5-12	24 x 10.5-12
Front Caster Wheel Size	13 x 6.5-6	13 x 6.5-6
Caster Arm Attachment	Bolt On	Bolt-On

  

Seat		
Seat	High-Back, Full-Mechanical Suspension Seat	High-Back, Full-Mechanical Suspension Seat
Fore-Aft Adjust	Seat Slide Lever	Seat Slide Lever

## ZT6000 Features & Benefits

[Expand all](#) ▾

**Performance** 4 ▾

**Comfort** 1 ▾

**Versatility** 2 ▾

**Serviceability** 1 ▾

**Durability** 1 ▾

## Related Models

[View All Zero-Turn Mowers](#) >

\*The prices advertised are suggested resale prices that Bobcat recommends to dealers for purposes of trying to ensure that Bobcat's products are price-competitive and that dealers have the proper incentives to market and service the products in accordance with Bobcat's brand standards. Bobcat reserves the right to change suggested resale prices, product specifications, and options at any time. The final sales price is determined independently by the selling dealer in its sole discretion. Pricing is country specific. Bobcat's suggested list prices are for products sold in the US only.

\*Offer ends 12/31/2023. Available at participating and eligible dealers only. Offer may vary by product type, series, model and select units in dealer's current inventory. Must take delivery from dealer stock by 12/31/2023. Offers available on new equipment in US and Canada only. Some restrictions apply. Length of contract and rate may vary. Monthly payment subject to change. Prior purchases not eligible. See dealer for details. Financing provided on approval of credit by authorized Bobcat finance providers to well-qualified buyers. All finance programs and rates are subject to final approval by the applicable Bobcat finance provider and are subject to change at any time without notice. Administrative fees may apply. Offer not available to government accounts, national accounts and municipal/utility bid customers. Bobcat Company reserves the right to extend or discontinue any of these programs at any time without prior notice.



**WARNING:** This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.